



Sigen EV DC Charging Module

- V2H power supply, ample backup energy
- V2G power transfer, ready for energy trading
- EV-supported home energy system black start
- Max. 25 kW stable bi-directional charging
- 150 V – 1000 V charging, wide EV compatibility
- Charge EV with 100% solar power
- Track & schedule charging on mySigen APP
- IP66 protection, maintenance free

Sigen EV DC Charging Module 12.5 / 25.0 kW

Preliminary

SigenStor EVDC	12.5	25.0	Units
DC Output			
Max. charging power	12.5	25	kW
Max. discharging power (V2H, V2G)	12.5	25	kW
Output voltage range	150 ~ 500 (CHAdeMO), 150 ~ 1000 (CCS1 / CCS2)		V
Max. output current	40	80	A
Charging interfaces	CHAdeMO / CCS1 / CCS2		
Protection			
Short-circuit protection	Supported		
Over / Under voltage protection	Supported		
Overload protection	Supported		
Over temperature protection	Supported		
Reverse polarity protection	Supported		
Welded contactor check	Supported		
General Data			
Dimensions (W / H / D)	700 / 270 / 260		mm
Weight	40		kg
Storage temperature range	-40 ~ 70		°C
Operating temperature range	-30 ~ 60		°C
Relative humidity range	5% ~ 95%		
Max. operating altitude	4000		m
Cooling	Smart air cooling		
Ingress protection rating	IP66		
Integrated charging cable length	5 / 7.5		m
Function			
Authentication	RFID card / Auto. charging (no authentication)		
Application	Bi-directional charging (V2H, V2G), Smart load management, Reservation		
User interfaces	LED indicator, APP, RFID / NFC reader		
Remote function	OTA, Remote diagnosis		
Communication	4G / Wi-Fi / FE		

* Sigen EV DC Charging Module needs to be used together with Sigen Energy Controller / Sigen Storage Controller.